

Built Stronger to Last Longer

Gooseneck

Trailer Mfg. Co., Inc.

Bumper Pull Stock



Features

Standard

- . 16' Long, 6' Wide, 6'2" Tall
- . 2 Butterfly Front Vents
- . Wood Floor
- . 2- 6000 lbs. Axles
- . Electric Brakes Both Axles
- . LT 235/85R 16 10 Ply Tires
- . Full Metal Front
- . 1 Crossgate
- . Slide Swing Tailgate
- . 2 5/16" V-Coupler
- . Full Escape Door
- . Bartop
- . Spare Tire and Wheel
- . Red or Black
- . 4- 1x3 Tube Sides
- . Brush Fenders

Optional

- . 5 Plank Sides
- . 6 Plank Sides
- . 7 Plank Sides
- . Pipe Sides
- . 5- 1x3 Tube Sides
- . 6- 1x3 Tube Sides
- . 7- 1x3 Tube Sides
- . Different Color
- . Canvas Top
- . Metal Top
- . Split Tailgate
- . 14' Trailer Length
- . 5' Trailer Width
- . 6'6" Bow Height



WWW.GOOSENECK.NET 800-688-5490

4400 East Hwy 21, Bryan TX 77808
Box 832 Bryan, TX 77806-0832
979-778-0034 * Fax 979-778-0615

"Gooseneck Trailer Mfg. Co., Inc. reserves the right to change the design, features, options, materials and/or specifications at any time, without notice, and without incurring any obligation for such changes. Contact Gooseneck Trailer Mfg. Co., Inc. to determine what is offered at the time of your order." 08/09
The GOOSENECK trademark is a registered trademark (U.S. Pat. & Tm. Off. Number 1,857,615) and may only be used to describe genuine Gooseneck Trailers